

Series	UDP-200 / 300 / 400			HSP-200 / 300		UHP-200A / 200 / 350 / 500			
Power/Rated Current	200W / 40A	300W / 60A	400W / 80A	200W / 40A	300W / 60A	200W / 40A	200W / 40A	300W / 60A	400W / 80A
Input Voltage Range	90~264VAC			90~264VAC	90~135VAC 180~264VAC	90~264VAC			
Output Voltage	4.2V / 4.6V / 5V			4.2V / 5V	2.8V / 4.2V / 5V	4.2V / 4.5V / 5V	3.3V / 4.2V / 5V		4.2V / 5V
Adjustable Output Voltage	0.1 V step size via DIP switch			VR adjustment		VR adjustment			
Efficiency(5V)	92%			88.5%	87%	88.5%	91%	90%	90%
Working Temp.	100%LOAD @50℃ 75%LOAD @70℃			100%LOAD @50℃ 60%LOAD @70℃	100%LOAD @50℃ 30%LOAD @70℃	100%LOAD @50℃ 60%LOAD @70℃			100%LOAD @40℃ 50%LOAD @70℃
Low Voltage Input Derating	<100VAC Derating			<110VAC Derating	<180VAC Derating	<180VAC Derating	<110VAC Derating		
Redundant Parallel Operation	√ · R version			X		X	√ · R version		
Protection	Conformal-Coated			Conformal-Coated		Semi-Potted			
Dimension(mm)	150*50*19	165*50*26	200*50*26	210*62*31	210*81*31	167*55*26	194*55*26	220*62*31	232*81*31
Warranty	3 years			3 years		3 years			